

CrystalView DVI Micro



SKU CRK-T1DFMDM
Produkt Verfügbarkeit
User
Ports
HE/U
DVI
VGA
Breite/width
Länge/length
Multiplattformfähig
IP-Zugriff
Verkabelung CatX/Koax
Connection PS2/USB
Audio
Access
Verkabelung CatX/LWL
Multi Video

- Miniature style directly connects to DVI connector
- Video resolution up to: 1920 x 1200 at 1000 feet (300m)
- SC type connector on unit connects to a single multi-mode fiber
- Auto-detect EDID information

SPECIFICATIONS

Dimensions	1.57" x 2.61" x 0.59" (40 x 66 x 15 mm)
(W x D x H)	
Weight	0.6 lb (0.25 kg)
Power	Transmitter: Powered by computer DVIRceiver: 100-240 VAC 50-60Hz, External adapter, +5V DC, 2A Standard: 5W
Distance	1920 x 1200: 1000' (300m)1600 x 1200: 1650' (500m)1280 x 1024: 2,300' (700m)
Connectors	Transmitter:Single-link DVI video: DVI male direct plug-inFiber: Single multi-mode fiber with SC connectorReceiver:Single-link DVI video: DVI male direct plug-inFiber: Single multi-mode fiber with SC connector
Environment	Operating temperature: 32°F-122°F (0°C-50°C)Storage temperature: -4°F-158°F (-20°C-70°C) Relative humidity: 20%-80%, non-condensing