

Translator VGA to HDMI



SKU

Translator VGA to HDMI

Produkt Verfügbarkeit

User

Ports

HE/U

DVI

VGA

Breite/width

Länge/length

Multiplattformfähig

IP-Zugriff

Verkabelung CatX/Koax

Connection PS2/USB

Audio

Access

Verkabelung CatX/LWL

Multi Video

- Convert and scale VGA video to HDMI
- Intuitive OSD control interface, accessible with either IR control or Mini USB control
- Output modes are RGB, YCbCr444, YCbCr442, selectable as 480p, 720p, 1080i and 1080p
- Maximum pixel rate is 165MHz
- Stereo and S/PDIF audio input is converted to HDMI audio output
- De-interlacer supported
- Supports noise reduction and video enhancement
- Video adjustments including under/over scan, aspect ratio and H/V mirror
- Active video area adjustment supported
- Firmware upgradeable via mini USB port
- Image control using adjustable contrast, brightness, saturation, hue, color tone, sharpness and edge enhancement
- Utilizes standard length VGA, audio and HDMI cables
- Mounting brackets included for easy installation, shelf or wall mountable
- Connect to DVI monitors using HDMI/DVI adapter

Dimensions

3.6" x 3.3" x 1.1" (92 x 83 x 28 mm)

(W x D x H)

Weight 0.55 lb (0.25 kg)

Power 100-240 VAC, 50-60Hz External adapter, 5V, 2A10W

Resolution 1920 x 1080

Distance Video: 25 feet (7.6m)

Connectors	Video in: 1x HD15 maleAudio in: 1x 3.5mm jackAudio in: 1x S/PDIF CoaxVideo out: HDMI femaleFW update: Mini-USB-BPower: Barrel jack
Controls	Unit power: Red LEDSignal present: Green LED
Environment	Operating temperature: 32°F-104°F (0°C-40°C)Storage temperature: -4°F-140°F (-20°C-60°C) Relative humidity: 20%-90%, non-condensing