


## Switched and Metered PDU Einphasig, 230V AC, 32A, 32 Ports 24 x IEC C-13 8 x IEC C-19

### Selecting a Power Distribution Unit (PDU)

The Enconnex PDU distributes power to devices in the rack and offers real-time phase and circuit breaker metering and network monitoring of power loads for overload avoidance, capacity and load balancing, and energy use optimization.

- Determine the IT equipment power requirements of each device.**
  - Identify the type of outlet needed, the power draw of the device, and whether redundancy of power in the rack is desired.
- Select the appropriate power input to support the IT load.**
  - Identify the plug type that can deliver the power needed per step 1.
- Choose the features needed for implementation in your system.**
  - Review the next three pages of this catalog for tips.

### PDU in Detail



**SKU**  
**Produkt Verfügbarkeit**  
**sockets**  
**voltage**  
**phases**  
**PDU Typ**

ECX-WV1224080-P  
Lieferzeit auf Anfrage  
C-13 & C-19 Kaltgeräte  
230 Volt  
einphasig

### Outlet Metered, Outlet Switched PDUs

Combining all the features of the Switched PDU and the Outlet Metered PDU, this is the ultimate in PDU technology for all your data center monitoring needs.

### Switched PDUs

In addition to the features of the Input Metered PDU, switched outlets allow power-up sequencing, remote reboot, and outlet access control.

### Input Metered PDUs

The Enconnex PDU distributes power to devices in the rack configured with premium high-temperature, branch-rated hydraulic-magnetic circuit breakers. Labeled outlets and circuit breakers allow easy identification of circuit configuration for reduced connectivity errors. Ultra-low profile design reduces space when installed in the IT cabinet and improves airflow efficiency.

In addition to the features of the **Basic PDU**, a hot-swappable network management card allows for future upgrades and enhanced MTTR. Up to 8 optional environmental sensors can be connected and managed through each PDU.