

Smart Master PIPS V36 (24)C13 (12)C19 HDOT Alt Phase 400V 16A



Artikelnummer/SKU	CS36CD-4NAF2S66
Produkt	Nein
Verfügbarkeit	
sockets	C-13 & C-19 Kaltgeräte
voltage	400 Volt
phases	dreiphasig
PDU Typ	Alternating Phase PDU

Server Technology Smart CDU

- High Density: Single-power input feed; (24) C13 and (12) C19 outlets per enclosure.
- Power Distribution: 400V 3-Phase, 16A power input options.
- Input Current Monitor: Precisely measure the aggregate current draw (in amps). On-site verification of the input current with the LED digital display. Remote verification via web browser or serial screen.
- IP Access & Security: Web interface, SSL, SSH, Telnet, SNMP, FTP, SNT, Syslog, LDAP, LDAPS, RADIUS, TACACS and RS-232 access
- Alerts: Provide automated SNMP-based alarms or email alerts for power and environmental conditions
- Environmental Monitoring: Each Smart CDU supports two external temperature & humidity probes and reports conditions through the user interface without the need for additional IP addresses
- Add an Expansion Module: Connect the Smart Expansion CDU (CL) to a Master unit (CS) for power monitoring of separate power circuits from a single IP address