

PDU Switched POPS, 0U, 24 x IEC C13, 6 X IEC 19 Outlets, 230V, 16A



SKU	SEV-6501A
Produkt Verfügbarkeit	
sockets	C-13 & C-19 Kaltgeräte
voltage	230 Volt
phases	einphasig
PDU Typ	Switched PDU

Inputs

Input Voltage: 208
 Input Plug: IEC C20 200-240V Inlet * Input Current: 20
 Input Current Rated: 16

Outputs

Connector: (24) x IEC 60320/C13
 North American Rating (C13): ≤ 12A @208V L-L (15A Peak)
 Global Rating (C13): ≤ 10A @230V L-L
 Connector: (6) x IEC 60320/C19
 North American Rating (C19): ≤ 16A @208V L-L (20A Peak)
 Global Rating (C19): ≤ 16A @230V L-L
 Locking outlets provide high-retention even for non-locking cords.

Branch Circuit Protection

UL489 compliant 2-pole, 20A trip circuit breakers, two (2) branches, rating: ≤ 16A @208-240V

Physical

Dimensions: 69.0 (1753.0 mm) tall x 2.2 (56.0 mm) wide x 2.25 (58.0 mm) deep

Environmental

Operating Environment: 32°F to 140°F / 0°C to 60 °C | 8%RH to 90%RH non-condensing | 6,500ft/2km elevation
 Storage Environment: -40°F to 185°F / -40°C to 85°C | 8%RH to 90%RH non-condensing | 50,000ft/15km elevation
 Quiescent / Unloaded Power Draw: <10W for all configurations

Communications & Security

10/100 Mbps Ethernet (RJ-45 connector), RS-232 serial (RJ-45 connector)
 Two (2) temperature/humidity sensor inputs (4P4C), Link port (RJ-12) - {also on Link PDU} Web-browser GUI and command-line interface (CLI): HTTP/HTTPS, TLSv1, SSHv2, Telnet, SNMPv2c and v3 (GET, SET, Traps), IPv4 and IPv6, LDAPv3/LDAPS, TACACS+, RADIUS, FTP/SFTP

Certifications

North American:

cTUVus Mark to UL 60950-1:2007 and CAN/CSA 22.2 No. 60950-1-07 + A1:2011 EMC to EN 55022 Class A, EN 55024, CISPR 22 Class A

FCC Class A, Part 15

Global:

TUV T-Mark to EN 60950-1:2006 + A11 + A1 + A12

EMC to EN 55022 Class A, EN 55024, CISPR 22 Class A CE Mark

RoHS/WEEE

Measurement Accuracy

Input Measurement Accuracy:

LED Current = $\pm 10\%$ at 0.1 amp (0.3 - 9.9 amps) and 1 amp (> 9.9 amps) resolution GUI Current = $\pm 1\%$ at 0.01 amp resolution (above 0.25 amp)

Voltage = $\pm 1\%$ at 0.1 volt resolution (nominal $\pm 10\%$)

Active Power = $\pm 1\%$ at 1 watt resolution

Apparent Power = $\pm 1\%$ at 1 volt-amp resolution Power Factor = $\pm 3\%$ at 0.01 resolution

Crest Factor = $\pm 10\%$ at 0.1 resolution

Energy = $\pm 1\%$ at 0.1 kilowatt-hour resolution

Output Measurement Accuracy

GUI Current = $\pm 1\%$ at 0.01 amp resolution (above 0.15 amp) Voltage = $\pm 1\%$ at 0.1 volt resolution (nominal $\pm 10\%$)

Active Power = $\pm 1\%$ at 1 watt resolution Apparent Power = $\pm 1\%$ at 1 volt-amp resolution Power Factor = $\pm 3\%$ at 0.01 resolution

Crest Factor = $\pm 10\%$ at 0.1 resolution

Energy = $\pm 1\%$ at 1 watt-hour resolution

Branch Measurement Accuracy

Current = $\pm 3\%$ at 0.01 amp resolution (above 0.5 amp)

Optional Accessories

EMTH-1-1 Combination Temperature/Humidity Probe, 10ft (3m)

EMCU-1-1B Environmental Monitor adding:

- Two (2) EMTH-1-1 temperature/humidity ports (one probe included)
- One (1) EMWS-1-1 water sensor port (probe sold separately)
- Four (4) dry contact (NO/NC) monitoring points
- One (1) 8-bit analog-to-digital converter (0 to 5VDC)

KIT-PRO2LINK-01M or -01D provides ability to link (2) additional PRO2 units KIT-STEYE-01 or -10 provides access to key metrics through Bluetooth

SPM (Sentry® Power Manager):

-
- Monitor and manage multiple PDUs from a single point
 - Monitor and manage alarm conditions
 - Create reports and trends on stored data
 - Analyze power usage per phase
 - Optional appliance or virtual version
 - VMware Ready2

Mounting Brackets

- Buttons (KIT-0020) included for tool-less mounting (see diagram)
- See the Mounting Bracket Guide for further suggestions
- Custom mounting options available. Contact your local Server Technology representative Cable Retention Devices for non-locking cords
- Ezip
- Cable Sleeve

* Order PTCORD separately. Choose L6-20P, CEE 7/7 Schuko, IEC60309 2P+PE, or BS1363