Vista HDMI 4K



SKU	KVM-4THD/4K
Produkt Verfügbarkeit	
User	1
Ports	4
HE/U	1
DVI	
VGA	
Breite/width	
Länge/length	
Multiplattformfähig	
IP-Zugriff	
Verkabelung CatX/Koax	CatX
Connection PS2/USB	USB
Audio	ja
Access	
Verkabelung CatX/LWL	CatX
Multi Video	

- Supports HDMI video resolutions up to 3840×2160@30Hz
- HDMI audio support, LPCM7.1, Dolby True HD, Dolby Digital Plus, and DTS-HD Master Audio
- HDCP 2.2 compliant
- Fully supports Windows, Mac, and Linux
- Supports USB2.0 devices and USB-HID keyboard/mouse
- Switchable stereo analog audio on all ports
- Access and control the switch via front panel push buttons, keyboard hot-keys or the serial RS-232 port
- Serial control interface via the DB9 serial port using the Rose RCS-4RS/D9 4-port remote control switch
- EDID learning and pass-through for all ports, enabling smooth and efficient video switching
- Independent switching and use of the KVM station and USB2.0 ports

- Complete keyboard/mouse emulation for error-free booting of connected PC’s/servers

SPECIFICATIONS

Dimensions (W x D x H)	12.5" x 6.34" x 1.71" (317 x 161 x 43.4 mm) (1U)
Weight	3.5 lb (1.6 kg)
Power	100-240 VAC 50-60HzExternal adapter, +5V, 4A20W
Resolution	HDMI: 1080p@60HzHDMI: 1080p @60HzHDMI 4K: 3840 x 2160 @30HzVGA: 2048 x 1536

Distance	CPU/KVM: 20 feet (6m)
Connectors	Video: HDMI femaleUSB 2.0 host: USB Type BKeyboard: USB Type AMouse: USB Type AUSB 2.0 device: Two USB Type AAudio: 1 x Stereo Audio 3.5mm per channelSerial: DB9F serial portPower: Barrel jack
Controls	Computer selection: Front panel (2x20 LCD) , hot-key, serial port or optionalTCP/IP
Environment	Operating temperature: 23°F–95°F (-5°C–35°C)Storage temperature: -4°F–185°F (-20°C–85°C)Relative humidity: 5%–90%, non-condensing