Multivideo DP

SKU	MDM-4T2DP-A1
Produkt Verfügbarkeit	
User	1
Ports	4
HE/U	1
DVI	
VGA	
Breite/width	
Länge/length	
Multiplattformfähig	
IP-Zugriff	
Verkabelung CatX/Koax	CatX
Connection PS2/USB	USB
Audio	ja
Access	
Verkabelung CatX/LWL	CatX
Multi Video	

- Quad-head or dual-head video input
- Output video can be DisplayPort or HDMI
- Resolutions up to 3840×2160 @ 30 Hz
- DisplayPort 1.1a compliant
- Full USB keyboard and mouse emulation to all computers provides switching without interruption
- Independent switching of KVM, peripheral USB devices, and audio
- Unit can be controlled using front panel push buttons, keyboard hot key commands, or RS-232 commands from an external controller
- Front panel LEDs indicate the active computer connection
- Can be used with any major operating system: Windows, Linux, MAC OS
- EDID pass-through enables smooth and efficient switching
- Mounts in a standard 19 inch rack

SPECIFICATIONS

Dimensions (W x D x H)	Dual-Head: 12.8" x 6" x 3" (325 x 152 x 76 mm)Quad-Head: 12.8" x 6" x 4.5" (325 x 152 x 114 mm)
Weight	Dual-Head: 4.4 lb (2 kg)Quad-Head: 5.7 lb (2.6 kg)
Power	100-240VAC, 50-60HzExternal Adapter 5V/4ADual-Head: 15WQuad-Head: 20W
Resolution	3840 x 2160 @30Hz
Distance	16ft (5m) each side
Connectors	Video:HDMI type A femaleKeyboard: USB Type AMouse: USB Type AUSB2.0 device: 2 x Type AUSB Host: USB Type BAudio: 3.5mm stereo speaker audio jackSerial: DB9F RS-232Power: 5VDC barrel jack

Controls	Front Panel Push Button (2)Select LED (4)Status LED (2)Keyboard hotkeySerial port control
Environment	Operating temperature: 23°F–95°F (-5°C–35°C)Storage temperature: -4°F–185°F (-20°C–85°C)Relative humidity: 5%–95%, non-condensing