

CrystalLink USB1.1 CATx Dual Port



SKU	CLK-2U1TP-40M
Produkt Verfügbarkeit	
User	1
Ports	2
HE/U	
DVI	
VGA	
Breite/width	
Länge/length	
Multiplattformfähig	
IP-Zugriff	
Verkabelung CatX/Koax	
Connection PS2/USB	USB
Audio	ja
Access	
Verkabelung CatX/LWL	
Multi Video	

- Extends two USB2.0 devices at USB1.1 speeds
- Supports full-speed (12Mbps) or low-speed (1.5Mbps) USB devices
- Interface powered Transmitter Unit, and self-powered Receiver Unit
- Plug and Play. No software drivers required
- Supports all major Operating Systems: Windows, MAC OS X, Linux
- Remote extender provides up to 400mA power to attached USB devices
- Robust ESD and EFT immunity for industrial environments

SPECIFICATIONS

Dimensions

(W x D x H) 2.17" x 3.34" x 0.87" (55 x 85 x 22 mm)

Weight 1 lb (0.5 kg)

Power Transmitter: USB powered Receiver: powered from TX unit USB, Device: receives 400mA when the TX unit is supplied with 800mA

USB Host Support XHCI (USB 3.0), EHCI (USB 2.0) and OHCI/UHCI (USB 1.1)

Distance 130' (40m)

Connectors Transmitter:USB host: USB Type A Link: RJ45 Receiver:USB device: (2) USB Type A(F) Link: RJ45

Environment Operating temperature: 32°F-122°F (0°C-50°C) Storage temperature: -4°F-158°F (-20°C-70°C), Relative humidity: 20%-80%, non-condensing