CrystalLink USB2.0 CATx Flex Power



SKU	CLK-1U2TPB-100M/FP/PE
Produkt Verfügbarkeit	
User	1
Ports	2
HE/U	
DVI	
VGA	
Breite/width	
Länge/length	
Multiplattformfähig	ja
IP-Zugriff	
Verkabelung CatX/Koax	
Connection PS2/USB	USB
Audio	ja
Access	
Verkabelung CatX/LWL	CatX
Multi Video	

- Uses standard solid core CATx cable, CAT5e or better
- Operates with USB1.1 and USB2.0 hosts
- Plug and play, no software drivers required
- Supports all major Operating Systems: Windows®, MAC OS X®, Linux®
- Remote extender provides up to 500mA power to a single attached USB device
- Attach up to 4 powered USB hubs for additional remote USB device support
- Mounting slots are on both units – allowing rack mounting using cable tie wraps

SPECIFICATIONS

Dimensions (W x D x H)	2.25" x 3.35" x 1.1" (57 x 85 x 28 mm)
Weight	1.35 lb (0.62 kg)
Power	100-240 VAC 50-60HzOne external adapter, +24V DC, 1A24W
USB Host Support	EHCI (USB 2.0) and OHCI/UHCI (USB 1.1)
Distance	330' (100m)
Connectors	Transmitter:USB host: USB Type BLink: RJ45Power: Barrel jack (24VDC)Receiver:USB device: Type ALink: RJ45Power: Barrel jack (24VDC)
Controls	Link status: Green LED on TX and RX
Environment	Operating temperature: 32°F–122°F (0°C–50°C)Storage temperature: -4°F–158°F (-20°C–70°C)Relative humidity: 20%–80%, non-condensing