

CrystalView DVI Micro



SKU	CRK-T1DFMDM
Produkt Verfügbarkeit	
User	
Ports	
HE/U	
DVI	
VGA	
Breite/width	
Länge/length	
Multiplattformfähig	
IP-Zugriff	
Verkabelung CatX/Koax	
Connection PS2/USB	
Audio	
Access	
Verkabelung CatX/LWL	
Multi Video	

- Miniature style directly connects to DVI connector
- Video resolution up to: 1920 x 1200 at 1000 feet (300m)
- SC type connector on unit connects to a single multi-mode fiber
- Auto-detect EDID information

SPECIFICATIONS

Dimensions

1.57" x 2.61" x 0.59" (40 x 66 x 15 mm)
(W x D x H)

Weight 0.6 lb (0.25 kg)

Power Transmitter: Powered by computer DVIREceiver: 100-240 VAC 50-60Hz, External adapter, +5V DC, 2AStandard: 5W

Distance 1920 x 1200: 1000' (300m)1600 x 1200: 1650' (500m)1280 x 1024: 2,300' (700m)

Connectors Transmitter:Single-link DVI video: DVI male direct plug-inFiber: Single multi-mode fiber with SC connectorReceiver:Single-link DVI video: DVI male direct plug-inFiber: Single multi-mode fiber with SC connector

Environment Operating temperature: 32°F-122°F (0°C-50°C)Storage temperature: -4°F-158°F (-20°C-70°C)Relative humidity: 20%-80%, non-condensing