

## QuadraVista UHD



**SKU** QV-4UHD  
**Produkt Verfügbarkeit**  
**User**  
**Ports**  
**HE/U**  
**DVI**  
**VGA**  
**Breite/width**  
**Länge/length**  
**Multiplattformfähig**  
**IP-Zugriff**  
**Verkabelung CatX/Koax**  
**Connection PS2/USB**  
**Audio**  
**Access**  
**Verkabelung CatX/LWL**  
**Multi Video**

- A multi-featured KVM switch with display of four concurrent HDMI 1.4 sources up to 4K30Hz on one UHD monitor
- Dynamic sizing and positioning of each image on freely adjustable windows with full-screen capability at 4K30Hz
- Implement multi-view display solutions on multiple UHD monitors using one set of keyboard and mouse with multiple units cascaded via HDMI, USB, and audio connections
- On-screen display of the video source label, video window border and intuitive GUI control
- HDCP compliant
- USB-HID touchscreen support
- Supports multiple user collaboration and user messaging on a networked environment
- Optional KM module allows full keyboard, mouse, and audio mixing control over the attached video source equipment
- Optional Video-over-IP module for transmission of visually lossless display of multiple Video-over-IP together with direct HDMI connections
- UHD video wall processing using an optional UHD-2HD converter module allows multiple images to be displayed across a 2x2 display array

### SPECIFICATIONS

|                        |                                                                        |
|------------------------|------------------------------------------------------------------------|
| Dimensions (W x D x H) | 6.9" x 10.3" x 1.75" (174 x 260 x 44.5 mm) 1U                          |
| Weight                 | 10.36 lb (4.7 kg)                                                      |
| Power                  | 100-240 VAC 50-60Hz, +12VDC 9AStandard power cord to IEC receptacle54W |
| Resolution             | HDMI: 3840 x 2160/30Hz                                                 |

---

|             |                                                                                                                                                                                                                                                                                                 |
|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Distance    | CPU/KVM: 25 feet (7.6m)                                                                                                                                                                                                                                                                         |
| Connectors  | Main card: 4 × HDMI type A female input 1 × HDMI type A female output 1 × RJ45 ethernet 2 × USB-A - HID 1 × USB-B - USB 2.0 1 × 3.5mm, analog stereo and mic KVM card: 4 × USB-B - USB 2.0 1 × USB-B - cascade Audio: stereo audio microphone, audio cascade Input: 6 × 3.5mm Output: 2 × 3.5mm |
| Controls    | 1 × LED (green) when power on                                                                                                                                                                                                                                                                   |
| Environment | Operating temperature: 32°F–104°F (0°C–40°C) Storage temperature: 14°F–122°F (-10°C–50°C) Relative humidity: 0%–80%, non-condensing                                                                                                                                                             |