

Einphasig, 230-240V, 16A, 8x IEC C-13



SKU	PX3-5190CR
Produkt Verfügbarkeit	
sockets	C-13 Kaltgeräte
voltage	230 Volt
phases	einphasig
PDU Typ	

FEATURES:

- Billing-Grade (+/- 1%) Energy Metering [kW, kVA, V, A, Power Factor] - per inlet, per outlet
- Remote Outlet Switching (Bi-State Latching Relays)
- Color, matrix LCD display
- Voltage, current, or active power (per line, or per receptacle / outlet);
- Alarms; Configuration information (name, ratings, IP / Networking information)
- Auto-flip orientation
- Field-Replaceable, hot-swappable network module with 536MHz processor, 16MB SPI Flash, and 64MB DDR2 RAM; Gigabit(10/100/1000) Ethernet port. Secondary, redundant Ethernet port. Redundant power sharing between network modules. Remote network monitoring via HTML, JSON-RPC, SSH, Telnet, MODBUS/TCP, and SNMPv3.
- Environmental monitoring [temp/humidity] capable of up to 32 sensors.
- Individual outlet numbers labeled on chassis.
- Automated deployment via TFTP, DHCP/PXE, SSH(CLI), or USB Flash Drives. WiFi Capable. USB Webcam Capable. iPad/iPhone/Android App.
- Tri-color status LED per receptacle.
- Max Dimensions 440mm x 183mm x 44mm (17.3in x 7.2in x 1.7in).
- Max Weight 5 kg.
- Maximum ambient temperature 60C at full load.