

## CoolRack CW Silent Water Cooling 7,45 kW, 800+150x1200x2100 mm



|                              |                     |
|------------------------------|---------------------|
| <b>SKU</b>                   | CR-8-MW-G-8-12-42-A |
| <b>Produkt Verfügbarkeit</b> |                     |
| <b>Belastbarkeit in kg</b>   |                     |
| <b>HE/U</b>                  | 42                  |
| <b>Breite/width</b>          | 800+185             |
| <b>Tiefe/depth</b>           | 1200                |
| <b>Höhe/height</b>           | 2100                |
| <b>kW</b>                    | 7,45                |
| <b>Segmentation</b>          |                     |

Direct-cooled server cabinet 42U an8d sound insulation consisting of a surface cooling unit in the rack with a cooling capacity of 7,45 kW

### Cooling medium - cold water ( CW) -

- Description and technical data in the server enclosure:
- Soundproof - noise reduction 38 dB
- Base frame, welded, with revolving round and Slotted
- Static load capacity up to 1548 kg
- Infinitely depth-adjustable 19" mounting angles with 42 U
- Max. 19" mounting depth 780 mm
- 1 x glazed door with three-point locking and rotating lever handle, lockable, circumferential seal, 3 x two-way hinges with 180° opening angle
- 1 x door made from solid steel with three-point locking and rotating lever handle, lockable, circumferential seal, 3 x two-way hinges with 180° opening angle

- 2 x side wall in inserting screws
- Base with leveling feet
- Removable hood with ventilation slots
- Removable cable entry panel
- Removable trim, side
- Roof module with cable inlet from brush strip
- Base module with cable inlet from brush strip
- Modesty panels and vertical airflow barrier between 19" mounting angles and side wall
- Powder coating RAL 7035, light gray
- Cooling Technology: Water cooling (cold water must be provided by the customer )
- Dimensions WxDxH 800 +150 mm x 1200 x 2100 mm ( Part No. \* 8-12-42 )
- Dimensions WxDxH 800 +150 mm x 1000 x 2100 mm ( Part No. \* 8-10-42 )

**Description and technical data of the surface cooling device:**

|                                      |               |
|--------------------------------------|---------------|
| cooling capacity                     | 7,45 kW       |
| recirculated air quantity inside ST3 | 1.400 m³/h    |
| power supply                         | 230V/1Ph/50Hz |
| Electr. power W                      | 9-222         |
| SPL Interior ST1                     | 32 dB(A)      |
| SPL Interior ST2                     | 44 dB(A)      |
| SPL Interior ST3                     | 47 dB(A)      |
| width                                | 1.250 mm      |
| depth                                | 670 mm        |
| height                               | 285 mm        |
| weight                               | 30 kg         |