

CoolRack CW Silent Water Cooling 10,26 kW, 800+150x1200x2100 mm



SKU	CR-11-MW-G-8-12-42-A
Produkt Verfügbarkeit	
Belastbarkeit in kg	
HE/U	42
Breite/width	800+185
Tiefe/depth	1200
Höhe/height	2100
kW	10,26
Segmentation	

Direct -cooled server cabinet 42U and sound insulation consisting of a surface cooling unit in the rack with a cooling capacity of 10,26 kW

Cooling medium - cold water (CW) -

- Description and technical data in the server enclosure:
- Soundproof - noise reduction 38 dB
- Base frame, welded, with revolving round and Slotted
- Static load capacity up to 1548 kg
- Infinitely depth-adjustable 19" mounting angles with 42 U
- Max. 19" mounting depth 780 mm
- 1 x glazed door with three-point locking and rotating lever handle, lockable, circumferential seal, 3 x two-way hinges with 180° opening angle
- 1 x door made from solid steel with three-point locking and rotating lever handle, lockable, circumferential seal, 3 x two-way hinges with 180° opening angle

- 2 x side wall in inserting screws
- Base with leveling feet
- Removable hood with ventilation slots
- Removable cable entry panel
- Removable trim, side
- Roof module with cable inlet from brush strip
- Base module with cable inlet from brush strip
- Modesty panels and vertical airflow barrier between 19" mounting angles and side wall
- Powder coating RAL 7035, light gray
- Cooling Technology: Water cooling (cold water must be provided by the customer)
- Dimensions WxDxH 800 +150 mm x 1200 x 2100 mm (Part No. * 8-12-42)
- Dimensions WxDxH 800 +150 mm x 1000 x 2100 mm (Part No. * 8-10-42)

Description and technical data of the surface cooling device:

cooling capacity	10,26 kW
recirculated air quantity inside ST3	1,906 m³/h
power supply	230V/1Ph/50Hz
Electr. power W	10-240
SPL Interior ST1	24 dB(A)
SPL Interior ST2	40 dB(A)
SPL Interior ST3	49 dB(A)
width	1.550 mm
depth	670 mm
height	285 mm
weight	36 kg