

RZ Pro Rack IP54 with active ventilation by fans 800x1000x2100



SKU	RZ-S-8-10-42V-IP54
Produkt Verfügbarkeit	
Belastbarkeit in kg	1600
HE/U	42
Breite/width	800
Tiefe/depth	1000
Höhe/height	2100
kW	
Segmentation	

RZ Pro Rack

- Base frame, welded, with surrounding circular -and- Slotted
- static load capacity up to 1548 kg
- infinitely depth-adjustable 19" mounting angles with 42 U
- max. 19" installation depth 840 mm
- 1x door with three-point locking and rotating lever handle, lockable
- peripheral seal
- 3x reciprocal hinges with 180° opening angle
- 1x door made of solid steel with three-point locking and rotating lever handle, lockable
- circumferential sealing IP54
- 3x reciprocal hinges with 180° opening angle
- 2x sidewall inserting screws,
- Base with leveling feet - with optional transport wheels

- Removable hood with ventilation slots
- Removable cable entry panel
- removable trim panels
- Roof module with cable inlet and two blow off fans, IP54
- Base module with cable entry and two front fans blowing in and dust filters
- Powder coating RAL 9005
- jet black (also available: RAL7035, light gray Article No. RZ-G-xx.)
- Weight incl. Packaging 185 kg (20 kg Pack.)