

TITANUS RACK · SENS® 88.9 mm height (2U) base unit



SKU	TITANUS RACK·SENS 2HE
Produkt Verfügbarkeit	
Belastbarkeit in kg	
HE/U	2
Breite/width	483
Tiefe/depth	670
Höhe/height	88,1
kW	
Segmentation	

Technical specifications:

Current consumption rest (at 24 V) 155 mA - 350 mA *

Current consumption Alarm (at 24 V) 255 mA - 535 mA * (plus 250 mA per extinguishing fan)

Monitored inputs / outputs

- Door contact
- Reset (reset input)
- Max. 5 temperature sensors *
- Extinguishing fan
- Cut-off
- Manual release
- Data A / B bus connection and 24 V power supply for external modules
- Network*

Potential-free relay outputs

- Pre-, main alarm per detector *
- Disorder
- Max. 5 programmable relay
- Triggered deletion
- Service (Separate)
- Contact load alarm / fault relay 1 A / 30 V DC

Integrated extinguishing agent container

Extinguishing Bowl capacity Max. 2 x 2 liters

Extinguishing agent Novec[™] 1230 from 3M[™] or on request: FM-200 (HFC-227ea)

Property shutdown integrated relay control

Weight (maximum configuration) 32 kg *

Dimensions (H x W x D mm) 88.1 x 483 x 670

Minimum required installation depth 900 mm

* Depending on the configuration level, extract from the technical manual TITANUS RACK · SENS®

3M and Novec are trademarks of 3M Company