

TITANUS RACK · SENS® 44.45 mm Overall height (1U) detection unit with maximum configuration



SKU	TITANUS RACK·SENS 1HE Maximalausbau
Produkt Verfügbarkeit	
Belastbarkeit in kg	
HE/U	1
Breite/width	483
Tiefe/depth	300
Höhe/height	43,6
kW	
Segmentation	

Technical specifications:

Current consumption rest (at 24 V) 135 mA * - 330 mA *

Current consumption Alarm (at 24 V) 235 mA * - 515 mA * (plus 250 mA per extinguishing fan)

Monitored inputs / outputs

- door contact
- Reset (reset input)
- Max. 5 temperature sensors *
- manual release
- Data A / B bus connection and 24 V power supply for external modules
- Network*

Potential-free relay outputs

- Pre-, main alarm per detector *
- disorder
- Max. 5 programmable relay
- triggered deletion
- Service (Separate)

Contact load alarm / fault relay 1 A / 30 V DC

Erasure on external extinguishing module * and external extinguishing agent container

Property shutdown via external module or disconnecting extinguishing

Weight (maximum configuration) about 6.4 kg *

Dimensions (H x W x D mm) 43.6 x 483 x 300

Minimum required installation depth 400 mm

* Depending on the configuration level, extract from the technical manual TITANUS RACK · SENS®