

TITANUS RACK · SENS® 88.9 mm height (2U) Maximum configuration



SKU

TITANUS RACK·SENS 2HE
Maximalausbau

Produkt Verfügbarkeit

Belastbarkeit in kg

HE/U

2

Breite/width

483

Tiefe/depth

670

Höhe/height

88,1

kW

Segmentation

Technical specifications:

Current consumption rest (at 24 V) 155 mA - 350 mA *

Current consumption Alarm (at 24 V) 255 mA - 535 mA * (plus 250 mA per extinguishing fan)

Monitored inputs / outputs

Door contact

- Reset (reset input)
- Max. 5 temperature sensors *
- Extinguishing fan
- Cut-off
- Manual release
- Data A / B bus connection and 24 V power supply for external modules
- Network*

Potential-free relay outputs

- Pre-, main alarm per detector *
- Disorder
- Max. 5 programmable relay
- Triggered deletion
- Service (Separate)

Contact load alarm / fault relay 1 A / 30 V DC
Integrated extinguishing agent container
Extinguishing Bowl capacity Max. 2 x 2 liters
Extinguishing agent Novec[™] 1230 from 3M[™] or on request: FM-200 (HFC-227ea)
Property shutdown integrated relay control
Weight (maximum configuration) 32 kg *
Dimensions (H x W x D mm) 88.1 x 483 x 670
Minimum required installation depth 900 mm

* Depending on the configuration level, extract from the technical manual TITANUS RACK · SENS®
3M and Novec are trademarks of 3M Company