

## CoolRack Silent Enclosure 800x1200x2100 mm



<b>SKU</b>	RZ-G-8-12-42-CROSA
<b>Produkt Verfügbarkeit</b>	delivery time on request
<b>Belastbarkeit in kg</b>	
<b>HE/U</b>	42
<b>Breite/width</b>	800
<b>Tiefe/depth</b>	1200
<b>Höhe/height</b>	2100
<b>kW</b>	
<b>Segmentation</b>	

Enclosure for CoolRack 800x1200x2100

Description and technical data of the box:

- Base frame, welded, with round round and long perforation
- Soundproof - noise reduction approx. 38 dB
- Static load capacity up to 1548 kg
- Infinitely depth-adjustable 19 "hole angle with 42 U
- Max. 19 "installation depth 780 mm
- 1xSight door with three-point lock and rotary lever handle, lockable, circumferential seal, 3 pcs. Reciprocal hinges with 180 ° opening angle
- 1x door made of solid steel plate with three-point lock and rotary lever handle, lockable, circumferential seal, 3 pcs. Hinges with 180 ° opening angle
- Base with leveling feet

- Roof module with cable entry from brush strip
- Ground module with cable entry from brush strip
- Powder coating RAL 7035, light gray
- Soundproofed with high-quality and highly inflammable acoustic foam D = 25 mm

The following noise levels have an impact on human behavior:

- At 45 dB (A), a relaxed conversation is more difficult.
- At 50 dB (A), those affected raise the voice.
- At 60 dB (A), people affected must speak loudly.
- If the load exceeds 65 dB (A), local residents change their behavior, that is, keep windows closed and balconies are no longer used.