

## RZ Pro Rack with active ventilation by fans 800x1000x2300



|                              |                |
|------------------------------|----------------|
| <b>SKU</b>                   | RZ-S-8-10-48-V |
| <b>Produkt Verfügbarkeit</b> |                |
| <b>Belastbarkeit in kg</b>   | 1600           |
| <b>HE/U</b>                  | 48             |
| <b>Breite/width</b>          | 800            |
| <b>Tiefe/depth</b>           | 1000           |
| <b>Höhe/height</b>           | 2300           |
| <b>kW</b>                    |                |
| <b>Segmentation</b>          |                |

### RZ Pro Rack

- Base frame, welded, with revolving round and slotted
- Static load capacity up to 1548 kg
- Infinitely depth-adjustable 19" mounting angles with 48 U
- Max. 19" mounting depth 840 mm 1x door with three-point locking and rotating lever handle, lockable
- Circumferential seal
- 3 x reciprocal hinges with 180° opening angle
- 1 x door made from solid steel with three-point locking and rotating lever handle, lockable Circumferential seal
- 3 x reciprocal hinges with 180° opening angle
- 2 x sidewall inserting screws
- Base with leveling feet - optional with transport wheels
- Removable hood with ventilation slots
- Removable cable entry panel
- Removable trim, side
- Roof module with cable inlet from brush strip and two blow off fans

- Powder coating RAL 9005 black ( also available: RAL7035 , light gray Item No. RZ -G -xx )
- Weight with packaging 195 kg ( 20 kg pack.)