

**19" AIR CONDITIONED SERVER RACK 42 U WITH AIR CONDITIONER 3000 W,
800+278X900X2000**



SKU	20650-SK-3000
Produkt Verfügbarkeit	
Belastbarkeit in kg	
HE/U	42
Breite/width	800+300
Tiefe/depth	900
Höhe/height	2000
kW	3.0
Segmentation	

19" climate cabinet with 3000 W air conditioning unit

- 19" cabinet pre-assembled
- with 3000 W side cooling unit
- with duct system for targeted air flow control
- Frame in plug-in system, can be dismantled
- Removable side panels
- Front viewing door
- Full rear door
- Lockable rotary lever handles
- Depth-adjustable 19" perforated brackets
- Earthing kit
- Roof module with cable inlet

- Floor module with cable inlet
- Leveling feet
- Special duct system for targeted airflow control
- Powder-coated RAL 7035 light gray

Side-mounted cooling unit 3000W

- Side-mounted cooling unit 3000W
- Rated voltage v-Hz 230-1-50/60
- with multicontroller
- Cooling capacity L35/L35: 3000W
- Power consumption L35/L35: 1190W
- Current consumption L35/L35: 5.2A
- Inrush current L35/L35: 16A
- Integrated condensate evaporation
- Ambient temperature range: +15...+55°C
- Refrigerant: 1200g R134a
- Protection class: IP 54 against the switch cabinet when used as intended
- Protection class: IP 34 against the environment when used as intended
- Housing: Galvanized sheet steel
- Hood: powder-coated
- Color of hood: RAL7035

Important note: The side air conditioner emits waste heat into the room. This can heat up the installation site! The installation location and thus the arrangement of the cooling unit must be selected in such a way that good on-site ventilation is ensured.

Translated with www.DeepL.com/Translator (free version)