

**19" AIR CONDITIONED SERVER RACK 42 U WITH AIR CONDITIONER 2500 W,
800+278X1000X2000**



SKU	20633-SK-2500
Produkt Verfügbarkeit	delivery time 1-2 weeks
Belastbarkeit in kg	
HE/U	42
Breite/width	800+300
Tiefe/depth	1000
Höhe/height	2000
kW	2.5
Segmentation	

19" server rack with air-condition 2500W

- assembled 19" rack
- with side refrigerator 2500 Watt
- Setting the plug-in system can be dismantled
- Removable sidewalls
- Glazed front door
- Full rear door
- Lever handles lockable
- depth adjustable 19 "mounting angles
- earthing kit
- Roof module with cable inlet

-
- Base module with cable inlet
 - Leveling
 - Special channel system for selective airflow control
 - Powder-coated RAL 7035 light gray

Side-mounted cooling unit 2500W

- Rated voltage 400/460 V AC
- With multi controller
- Cooling capacity L35/L35: 2500W
- Power consumption L35/L35: 1048W
- Current consumption L35/L35: 2,49A
- Inrush current L35/L35: 16A
- Integrated condensate evaporation
- Ambient temperature range: +15.+55° C
- Refrigerant: 1200g R134a
- Protection class: IP 54 towards the cabinet when used as intended
- Protection class: IP34 against the environment when used as intended
- Housing: galvanized sheet steel
- Hood: powder-coated
- Color of the hood: RAL7035
- Weight: 71 kg

Important note: The waste heat of the cooling unit is discharged into the surrounding space. Good ventilation and extraction system in the room is important.