

19" Server Cabinet 25 U with top air A/C unit 4000 W, 800x1000x1200 +470



SKU	20656-DK-4.2
Produkt Verfügbarkeit	delivery time 1-2 weeks
Belastbarkeit in kg	
HE/U	25
Breite/width	800
Tiefe/depth	1000
Höhe/height	1200+470
kW	4.0
Segmentation	

19" Server Climate Cabinet with air conditioning unit with 4000W

- Glazed front door
- Full rear door
- Rotary lever handles lockable
- Removable side panels
- Stable depth-adjustable 19" mounting angles 4 x 25 U
- Max. 19" mounting depth 710 mm
- Cable entry in a base module
- Earthing kit
- Leveling feet
- Air Ducts for increased airflow control
- Roof air conditioner 4000 W
- Operating voltage Volt **400** Hz, 50-60
- Pluggable terminal strip for power connection
- Powder coating RAL7035 light gray

Note to the site :

- The location and thus the arrangement of the heat must be selected so that good ventilation is ensured.

- Depending on the location of the system of distance on several directly mounted adjacently to the wall should be at least 200 mm.
- The refrigerator must be installed and operated in a horizontal position (max. deviation: 2 °).
- The site must be free from excessive dirt and moisture.
- The ambient temperature must not be higher than 55 ° C.
- A condensate drain must be enabled.
- The network connection specifications on the nameplate of the unit must be ensured.

Roof Top Cooling Unit 4000W

- Cooling unit for rooftop
- with Multi-Controller
- Rated voltage 400 V AC 3~
- Cooling capacity L35/L35: 4000W
- Power consumption L35/L35: 1618W
- Power consumption L35/L35: 7,07A
- Inrush current L35/L35: 17,1A
- integrated condensate evaporation
- ambient temperature range: +15...+55° C
- refrigerant: 1250g R134a
- protection class: IP 54 towards the control cabinet when used as intended
- Protection class: IP34 against the environment when used as intended
- Housing: galvanized sheet steel
- Hood: powder-coated
- Color of the hood: RAL7035
- Weight: 77