

19" Server Cabinet 25 U with top air A/C unit 4000 W, 800x1200x1200 +470



SKU	20521-DK-4.2
Produkt Verfügbarkeit	delivery time 1-2 weeks
Belastbarkeit in kg	
HE/U	25
Breite/width	800
Tiefe/depth	1200
Höhe/height	1200+470
kW	4.0
Segmentation	

19" Server Climate Cabinet with air conditioning unit with 4000W

- Glazed front door
- Full rear door
- Rotary lever handles
- Lockable
- Removable side panels
- Stable depth-adjustable 19" mounting angles 4 x 25 U
- Max. 19" mounting depth 910 mm
- Cable entry in base module
- Earthing kit Levelling feet
- Air Ducts for increased airflow control
- Roof air conditioner 4000 W Operating voltage Volt 400 Hz, 50-60
- Pluggable terminal strip for power connection
- Powder coating RAL7035 light gray

Note to the site :

- The location and thus the arrangement of the heat must be selected so that good ventilation is ensured.
- Depending on the location of the system of distance on several directly mounted adjacently to the wall should be at least 200 mm.

-
- The refrigerator must be installed and operated in horizontal position (max. deviation: 2 °).
 - The site must be free from excessive dirt and moisture.
 - The ambient temperature must not be higher than 55 ° C.
 - A condensate drain must be enabled.
 - The network connection specifications on the nameplate of the unit must be ensured.