

19" Server Cabinet 25 U with top air A/C 2000 W, 800x1200x1200 +415



SKU	20521-DK-2.1
Produkt Verfügbarkeit	delivery time 1-2 weeks
Belastbarkeit in kg	
HE/U	25
Breite/width	800
Tiefe/depth	1200
Höhe/height	1200+415
kW	2.0
Segmentation	

19" Server Climate Cabinet with air conditioning unit with 2000W

- Glazed front door
- Full rear door
- Rotary lever handles
- Lockable
- Removable side panels
- Stable depth-adjustable 19" mounting angles 4 x 25 U
- Max. 19" mounting depth 910 mm
- Cable entry in a base module
- Earthing kit Levelling feet
- Air Ducts for increased airflow control
- Roof air conditioner 2000 W Operating voltage Volt 230 Hz, 50-60
- Pluggable terminal strip for power connection
- Powder coating RAL7035 light gray

Note to the site :

- The location and thus the arrangement of the heat must be selected so that good ventilation is ensured.

- Depending on the location of the system of distance on several directly mounted adjacently to the wall should be at least 200 mm.
- The refrigerator must be installed and operated in a horizontal position (max. deviation: 2 °).
- The site must be free from excessive dirt and moisture.
- The ambient temperature must not be higher than 55 ° C.
- A condensate drain must be enabled.
- The network connection specifications on the nameplate of the unit must be ensured.

Roof-mounted cooling unit 2000W

- Rated voltage 230V AC
- cooling capacity L35/L35: 2000W
- with Multi-Controller
- Power consumption L35/L35: 1049W
- Power consumption L35/L35: 6,2A
- inrush current L35/L35: 16,8A
- integrated condensate evaporation
- ambient temperature range: +15...+55° C
- refrigerant: 750g R134a
- Protection class: IP 54 towards the control cabinet when used as intended
- Protection class: IP34 against the environment when used as intended
- Housing: galvanized sheet steel
- Hood: powder-coated
- Color of the hood: RAL7035
- Weight: 46