

19" Server Cabinet 42 U with top air A/C unit 1000 W, 800x1200x2000 +415



SKU	20688-DK-1.2
Produkt Verfügbarkeit	delivery time 1-2 weeks
Belastbarkeit in kg	
HE/U	42
Breite/width	800
Tiefe/depth	1200
Höhe/height	2000+415
kW	1.0
Segmentation	

19" Server Climate Cabinet with air conditioning unit with 1000W

- Glazed front door
- Full rear door
- Rotary lever handles
- Lockable
- Removable side panels
- Stable depth-adjustable 19" mounting angles 4 x 42 U Max. 19" mounting depth 910 mm
- Cable entry in a base module
- Earthing kit
- Leveling feet
- Air Ducts for increased airflow control
- Roof air conditioner 1000 W
- Operating voltage Volt 230 Hz, 50-60
- Pluggable terminal strip for power connection
- Powder coating RAL7035 light gray

Note to the site :

- The location and thus the arrangement of the heat must be selected so that good ventilation is ensured. `
- Depending on the location of the system of distance on several directly mounted adjacently to the wall should be at least 200 mm.
- The refrigerator must be installed and operated in a horizontal position (max. deviation: 2 °).

- The site must be free from excessive dirt and moisture.
- The ambient temperature must not be higher than 55° C.
- A condensate drain must be enabled.
- The network connection specifications on the nameplate of the unit must be ensured.

Roof Top Cooling Unit 1000W

- Cooling unit for roof mounting
- with multi-controller
- Rated voltage 230 V AC
- Cooling capacity L35/L35: 1000W
- Power consumption L35/L35: 663W
- Power consumption L35/L35: 3,98A
- inrush current L35/L35: 14,8A
- integrated condensate evaporation
- ambient temperature: +15...+55°C
- refrigerant: 400g R134a
- protection class: IP 54 towards the control cabinet when used as intended
- Protection class: IP34 against the environment when used as intended
- Housing: galvanized sheet steel
- Hood: powder-coated
- Color of the hood: RAL7035
- Weight: 35 kg