

Vista LC DVI



SKU KVM-12TDVI-K1
Produkt Verfügbarkeit
User 1
Ports 4
HE/U 1
DVI ja
VGA

Breite/width Länge/length

Multiplattformfähig

IP-Zugriff

Verkabelung CatX/Koax CatX
Connection PS2/USB USB
Audio ja

Access

Verkabelung CatX/LWL CatX

Multi Video

- Easy to use, fully featured 12-port digital KVM switch in a 1U chassis
- Handles all DVI video resolutions up to 1920×1200
- The local console port supports DVI-D video, USB-HID keyboard and mouse, and stereo analog speakers
- Each CPU port has a DVI-D connector and a USB B-Type connector that supports keyboard, mouse, and audio signals
- The product kit includes six CPU combo cables (6ft, 2.0m length)
- Supports VESA DDC2B emulation & TMDS signal pass-through
- Switching control is operated by keyboard hotkeys or front panel push-buttons
- Front panel LED's indicate connected CPU ports and the current active channel
- Can be integrated into several models of Rose RackView KVM Drawer products

SPECIFICATIONS

Dimensions

 $(W \times D \times H)$ 17.4" × 6.7" × 1.73" (443 × 171 × 44 mm) (1U)

Weight 5.5 lb (2.5 kg)

Power 100-240 VAC 50-60HzExternal adapter, +12V12W

Resolution Single-link DVI: 1920 x 1200
Distance CPU/KVM: 10 feet (3.0m)

Video: DVI femaleKeyboard: USB Type AMouse: USB Type AAudio: 3.5mm outputAudio Input:

combined with cablePower: Barrel jack



Controls Computer selection: Front panel or hot-keyCPU select: Push-button per portCPU select: Green LED,

active linkCPU status: Blue LED - connected PC

Operating temperature: 32°F-132°F (0°C-55°C)Storage temperature: -4°F-140°F (-

20°C-60°C)Relative humidity: 5%–90%, non-condensing