

Vista DP



SKU	KVM-4TDPHM-A1
Produkt Verfügbarkeit	
User	1
Ports	4
HE/U	1
DVI	ja
VGA	ja
Breite/width	
Länge/length	
Multiplattformfähig	
IP-Zugriff	
Verkabelung CatX/Koax	CatX
Connection PS2/USB	USB
Audio	ja
Access	
Verkabelung CatX/LWL	CatX
Multi Video	

- Supports DisplayPort video resolutions up to 3840×2160@30Hz
- Two models: DisplayPort in with DisplayPort or HDMI out
- Fully supports Windows, Mac, and Linux
- Supports USB2.0 devices and USB-HID keyboard/mouse
- Switchable stereo audio
- Access and control the switch via front panel push buttons, keyboard hot-keys or the serial RS-232 port
- Serial control interface via the DB9 serial port using the Rose RCS-4RS/D9 4-port remote control switch
- EDID learning and pass-through for all ports, enabling smooth and efficient video switching
- Independent switching and use of the KVM station and USB2.0 ports
- Complete keyboard/mouse emulation for error free booting of connected PC's/servers
- DVI and HDMI video can be supported by using suitable cable adapters

SPECIFICATIONS

Dimensions

(W x D x H) 12.7" x 6" x 2" (324 x 152 x 50 mm) (1U)

Weight 3.75 lb (1.7 kg)

Power 100-240 VAC 50-60Hz External adapter, +5V, 4A20W

Resolution DisplayPort: 3840 x 2160@30Hz HDMI: 3840 x 2160@60Hz

Distance CPU/KVM: 20 feet (6m) User/KVM: 20ft (6.0m)

Connectors	Video: DisplayPort femaleUSB 2.0 host: USB Type BKeyboard: USB Type AMouse: USB Type A USB 2.0 device: Two USB Type AAudio: 3.5mm stereo speakerSerial: DB9F serial portPower: Barrel jack
Controls	Computer selection: Front panel, hot-key or serial port
Environment	Operating temperature: 23°F-95°F (-5°C-35°C)Storage temperature: -4°F-185°F (-20°C-85°C) Relative humidity: 5%-90%, non-condensing