

## CrystalLink USB1.1 CATx



SKU CLK-1U1TP-40M

Produkt Verfügbarkeit

**User** 1 **Ports** 1

HE/U DVI VGA

Breite/width Länge/length

Multiplattformfähig

**IP-Zugriff** 

Verkabelung CatX/Koax CatX
Connection PS2/USB USB
Audio ja

Access

Verkabelung CatX/LWL CatX

Multi Video

- Extends full-speed USB 1.1 up to 130 feet (40 meters) over CATx cable
- Can extend low speed USB HID devices such as keyboard and mouse up to 275 feet (84 meters)
- Will also extend USB 2.0 devices, but at USB 1.1 speeds
- Supports full speed (12Mbps) or low speed (1.5Mbps) USB devices
- Transmitter unit powered by computer USB, Receiver unit powered by Transmitter unit
- Plug and play, no software drivers required
- Supports all major Operating Systems: Windows, Mac OS X, Linux
- Receiver Unit supplies up to 400mA power to USB devices
- Connect up to three self-powered USB hubs to the Receiver to support more USB devices
- Robust ESD and EFT immunity for industrial environments

## **SPECIFICATIONS**

Dimensions (W x D x H) 1.57" x 3.34" x 0.98" (40 x 85 x 25 mm)

Weight 1.35 lb (0.62 kg)

Transmitter: USB poweredReceiver: powered from TX unitUSB Device: receives 400mA when the

TX unit is supplied with 600mA

**USB Host** 

Support EHCI (USB 2.0) and OHCI/UHCI (USB 1.1)

Distance 130' (40m)

Connectors Transmitter: USB host: USB Type ALink: RJ45Receiver: USB device: USB Type A(F)Link: RJ45

Operating temperature: 32°F–122°F (0°C–50°C)Storage temperature: -4°F–158°F (-

20°C-70°C)Relative humidity: 20%-80%, non-condensing