

CrystalView EX HDMI Multi



SKU	CrystalView EX HDMI Multi
Produkt Verfügbarkeit	
User	
Ports	
HE/U	
DVI	
VGA	
Breite/width	
Länge/length	
Multiplattformfähig	
IP-Zugriff	
Verkabelung CatX/Koax	
Connection PS2/USB	
Audio	
Access	
Verkabelung CatX/LWL	
Multi Video	

- Extends up to four HDMI video signals and USB 2.0 up to 330' (100m)
- Uncompressed video resolution up to 1920 x 1200
- Three remote high-speed USB 2.0 device ports supplying 500ma power
- USB 2.0 throughput of up to 40 Mbps
- Supports audio via USB or optional dedicated channel
- Use USB keyboards, mice, printers, scanners, flash drives, audio devices, touch screens, game controllers, and many more USB devices

SPECIFICATIONS

Dimensions	Mini Chassis: 9" x 5.7" x 1.73" (228 x 144 x 44 mm) (1U) B Chassis: 16.7" x 4.85" x 1.75" (424 x 123 x 44.5 mm) (1U)
Weight	Mini Chassis: 4.4 lb (2 kg) B Chassis: 6 lb (2.7 kg)
Power	100-240 VAC 50-60Hz External adapter, +5V, 4A-9A, grounded Dual: 15W Triple: 30W Quad: 45W
Resolution	HDMI: uncompressed 1080p, 1920x1200, 4K 30, 2D/3D depth, 36 bit color Deep color, x.v.color
USB2.0 speed	Up to 40Mbps
Distance	HDMI/USB2.0: 330' (100m)
Connectors	Multi-Head Version: Transmitter: HDMI video: HDMI female, one per port USB host: USB Type B Link: RJ45 jack, one per port Power: Barrel jack Receiver: HDMI video: HDMI female, one per port USB device: Three USB Type A, 500ma each Link: RJ45 jack Power: Barrel jack Quad-Rack Version: Transmitter: HDMI video: HDMI female, one per port USB host: USB Type B, one per port Link: RJ45 jack, one per port Power: Barrel jack Receiver: HDMI video: HDMI female, one per port USB device: Three USB Type A, 500ma on each port Link: RJ45 jack Power: Barrel jack

Controls	Unit power: Green LED per portLink active: Green LED per portVideo active: Green LED per portUSB status: Green LED per port
Environment	Operating temperature: 32°F–104°F (0°C–40°C)Storage temperature: -4°F–158°F (-20°C–70°C) Relative humidity: 20%–80%, non-condensing