

QuadraVista HDMI 4K60



SKU	QV-4x1HM-4K60
Produkt Verfügbarkeit	
User	
Ports	
HE/U	
DVI	
VGA	
Breite/width	
Länge/length	
Multiplattformfähig	
IP-Zugriff	
Verkabelung CatX/Koax	
Connection PS2/USB	
Audio	
Access	
Verkabelung CatX/LWL	
Multi Video	

- Displays up to four HDMI video sources on a single monitor
- Input resolutions from 640×480@60Hz to 1920×1200@60Hz
- Supports HDMI 2.0 output resolution up to 4K2K@60Hz (4:4:4 8 bits)
- Window size and position are software adjustable
- HDCP 1.4 compliant
- Analog stereo audio output
- Output display parameters such as layout, resolution, titles, and borders are software controllable
- Up to eight different layouts can be saved
- Resize, position, zoom, pan, and blend output video
- Configure output through RS-232 or Ethernet
- 28 key IR remote control
- Rotation of input image by +90° or -90°
- Supports pixel by pixel mapping in a 2 x 2 configuration
- Automatically upscale 1920×1080@60Hz output resolution to 4K2K
- Two EDID selections, and custom EDID can be loaded from file
- Firmware updates via configuration software
- Software management package included with the product

SPECIFICATIONS

Dimensions
15.3" x 8.8" x 1.6" (30 x 224 x 42 mm) 1U
(W x D x H)

Weight 5.2 lb (2.4 kg)

Power	100-240 VAC 50-60HzExternal adapter, +12V DC, 5A9W
Resolution	HDMI Input: 1920 x 1200/60HzHDMI Output: Up to 4K2K@60Hz (4:4:4. 8 bits)
Distance	CPU/Switch: 10 feet (3m)
Connectors	Computer ports:4 x HDMI video in: HDMI Type AConsole port:1 x HDMI video out: HDMI Type AStereo Audio: 3.5mm jack (L/R)Other:Network: RJ45 EthernetSerial RS232 (D9F)Power: 12V,5A
Controls	via included software
Environment	Operating temperature: 32°F-104°F (0°C-40°C)Storage temperature: -4°F-140°F (-20°C-60°C) Relative humidity: 20%-90%, non-condensing