

QuadraVista UHD



SKU	QV-4UHD
Produkt Verfügbarkeit	
User	
Ports	
HE/U	
DVI	
VGA	
Breite/width	
Länge/length	
Multiplattformfähig	
IP-Zugriff	
Verkabelung CatX/Koax	
Connection PS2/USB	
Audio	
Access	
Verkabelung CatX/LWL	
Multi Video	

- A multi-featured KVM switch with display of four concurrent HDMI 1.4 sources up to 4K30Hz on one UHD monitor
- Dynamic sizing and positioning of each image on freely adjustable windows with full-screen capability at 4K30Hz
- Implement multi-view display solutions on multiple UHD monitors using one set of keyboard and mouse with multiple units cascaded via HDMI, USB, and audio connections
- On-screen display of the video source label, video window border and intuitive GUI control
- HDCP compliant
- USB-HID touchscreen support
- Supports multiple user collaboration and user messaging on a networked environment
- Optional KM module allows full keyboard, mouse, and audio mixing control over the attached video source equipment
- Optional Video-over-IP module for transmission of visually lossless display of multiple Video-over-IP together with direct HDMI connections
- UHD video wall processing using an optional UHD-2HD converter module allows multiple images to be displayed across a 2x2 display array

SPECIFICATIONS

Dimensions (W x D x H)	6.9" x 10.3" x 1.75" (174 x 260 x 44.5 mm) 1U
Weight	10.36 lb (4.7 kg)
Power	100-240 VAC 50-60Hz, +12VDC 9AStandard power cord to IEC receptacle54W
Resolution	HDMI: 3840 x 2160/30Hz

Distance	CPU/KVM: 25 feet (7.6m)
Connectors	Main card:4 × HDMI type A female input1 × HDMI type A female output1 × RJ45 ethernet2 × USB-A - HID1 × USB-B - USB2.01 × 3.5mm, analog stereo and micKM card:4 × USB-B - USB2.01 × USB-B - cascadeAudio: stereo audio microphone, audio cascadeInput: 6 × 3.5mmOutput: 2 × 3.5mm
Controls	1 ×LED (green) when power on
Environment	Operating temperature: 32°F-104°F (0°C-40°C)Storage temperature: 14°F-122°F (-10°C-50°C) Relative humidity: 0%-80%, non-condensing