

## VideoSplitter HDMI 4K60



|                              |                         |
|------------------------------|-------------------------|
| <b>SKU</b>                   | VideoSplitter HDMI 4K60 |
| <b>Produkt Verfügbarkeit</b> |                         |
| <b>User</b>                  |                         |
| <b>Ports</b>                 |                         |
| <b>HE/U</b>                  |                         |
| <b>DVI</b>                   |                         |
| <b>VGA</b>                   |                         |
| <b>Breite/width</b>          |                         |
| <b>Länge/length</b>          |                         |
| <b>Multiplattformfähig</b>   |                         |
| <b>IP-Zugriff</b>            |                         |
| <b>Verkabelung CatX/Koax</b> |                         |
| <b>Connection PS2/USB</b>    |                         |
| <b>Audio</b>                 |                         |
| <b>Access</b>                |                         |
| <b>Verkabelung CatX/LWL</b>  |                         |
| <b>Multi Video</b>           |                         |

- Distributes a single HDMI video signal to multiple displays
- Three models with either 2, 4, or 8 HDMI outputs
- HDMI 2.0a compliant
- HDCP 2.2 and 1.4 compliant
- Video capability 4K2K@60 4:4:4 8bits and HDR 4K2K@60 4:2:0 10bit
- Video bandwidth: 18Gbps
- Video supports all 3D modes, xvYCC, x.v.Color, and Deep Color
- Audio support includes Dolby Digital, DTS-HD, and Dolby TrueHD audio
- Rotary dial to setup built-in EDID or EDID learning from display
- Mini-USB connector to update firmware
- Cascading feature to increase number of output displays
- Built-in surface mounting bracket

### SPECIFICATIONS

|            |                                                                                                                                     |
|------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Dimensions | 8-port: 9.6" x 3.9" x 1" (243 x 98 x 25 mm)4-port: 6.1" x 3.3" x 1" (154 x 83 x 25 mm)2-port: 4.4" x 2.5" x 1" (113 x 62.5 x 25 mm) |
| Weight     | 8-port: 0.4 lb (0.88 kg)4-port: 0.3 lb (0.583 kg)2-port: 0.2 lb (0.463 kg)                                                          |
| Power      | 90-240 VAC 50-60HzExternal adapter, +5VDC8-port/4-port: 4A2-port: 2A8-port: 20W4-port: 15W2-port: 10W                               |
| Resolution | HDMI 2.0a compliantHDMI: 3840x2160: 24-bit RGB 4:4:4HDMI: 3840x2160: 36-bit YCbCr 4:2:0                                             |
| Distance   | Video: 10 feet (3m)                                                                                                                 |
| Connectors | Video Input: HDMI Type A femaleVideo Output: 2, 4, or 8 HDMI Type A FemalePower: Screw-in barrel jack                               |

Controls      Power: Red LEDVideo ready: Green LEDRotary Dial: EDID mode

Environment      Operating temperature: 32°F-104°F (0°C-40°C)Storage temperature: -4°F-140°F (-20°C-60°C)  
Relative humidity: 20%-90%, non-condensing