

19" IP 55 dust and water-proof wall housing 12U



SKU	OW-12HE-IP55
Produkt Verfügbarkeit	delivery time 1-2 weeks
Belastbarkeit in kg	
HE/U	12
Breite/width	600
Tiefe/depth	450
Höhe/height	713
kW	
Segmentation	

19 "IP 55 wall housing for industrial use 12 U

(Mini server cabinet)

IP55 (Outdoor) wall housings for industrial applications.

Accordance with protection against water and dust. Protection class IP55.

- 1.5 mm strong sheet steel with high load capacity
- Load capacity: 100 kg
- 3-point locking system with lockable swing handle
- Cable entries: 2x PG21, PG48 1x, 2x PVC Blind cap (28 mm diameter)
- Numbered 19 "mounting profiles on the front, adjustable in depth
- Integrated air filter housing to fresh air inlet (protection against water and dust ingress protection acc. IP 54)
- Front door with ground and two welded, strengthening beams in U-shape Incl. fastening material
- Available scope Reichers Accessories
- Size (HxWxD) 713/600/450 mm
- Color: light gray, RAL 7035
- HE: 9
- Load capacity: 100 kg

The 12U IP55 outdoor wall housings for industrial applications based on EN 60529 compliant IP55 protection class and is thus protected from water ingress and dust ingress. The ventilation units and filter internals are based on the protection class IP54. Best Performance offer the wall housing including through the 3-point locking system with lockable Schwenkhebelgriffund insulated cable inputs. Integrated air filter housing to fresh air inlet (protection against water and dust ingress-gem. IP54).

