

19" IP 55 dust and water-proof wall housing 12U



SKU	OW-12HE-600-IP55
Produkt Verfügbarkeit	delivery time 1-2 weeks
Belastbarkeit in kg	
HE/U	12
Breite/width	600
Tiefe/depth	600
Höhe/height	713
kW	
Segmentation	

19 "IP 55 wall housing for industrial use 12 U

(Mini server cabinet)

Technical description:

- Protection class IP 55
- Lockable steel front door with swivel lever handle
- 140 ° door opening angle
- 3-point four-point locking of the front door
- Front door with earthing and two welded, strengthening U-shaped beams and seal
- 483 mm (19 ") profile rails mounted on the front inside the cabinet, galvanized
- 483 mm (19 ") profile rails are adjustable in depth and with marking of the height unit
- Mistake
- 1.5 mm robust steel sheet with high load capacity, powder-coated
- Individually welded housing for more stability
- Cable entries in the floor: 2x M32, 1x M63, 2x PVC blind cap (with 28 mm diameter)
- Canopy with hot air fan modules to be installed provides hot air discharge from the housing
- Integrated ventilation filter housings ensure fresh air intake
- incl. 4 pieces of 3 mm mounting brackets for wall mounting as well as suitable screws
- and washers
- Min.-max installation depth for components: 142-500 mm
- Color gray
- Width: 600
- Version: with fixed frame
- Height in mm: 713
- Depth in mm: 600
- Color: RAL7035 light gray
- Number of doors: 1

- Type of ventilation: passive
- Material: steel
- Number of height units (U): 12
- With base: no
- Degree of protection (IP): IP55
- Surface finish: powder-coated