

19" two-section acoustic wall cabinet with 2 fans, RAL9005 black, 20U



SKU	WE2056-A-S
Produkt Verfügbarkeit	
Belastbarkeit in kg	
HE/U	20
Breite/width	600
Tiefe/depth	600
Höhe/height	998
kW	
Segmentation	

Technical Details:

- Lining with high-quality flame-retardant acoustic foam
- Active ventilation: via 2 fans in the roof
- Protection rating IP20
- Lockable safety-glass door with steel frame
- 210° door opening angle
- Single-point locking on the front door
- Side panels are lockable and removable
- 483 mm (19") mounting rails installed at the front and rear inside the cabinet, galvanized
- 483 mm (19") mounting rails are depth-adjustable and marked with height units
- Maximum installation depth: 450 mm
- Cable entry at the rear and bottom with plastic cover, and at the top with sliding cover
- Roof prepared for installation of a fan module (pre-punched cutouts)
- Ventilation slots for active and passive air intake and exhaust
- Multiple grounding points inside the cabinet for installed components
- Includes installation kit (screws, cage nuts, washers)
- Delivered fully assembled
- Installation depth for components min.-max.: 320-450 mm
- IP protection class: IP20
- Color: black, RAL9005
- Depth: 600 mm
- Front door: single-leaf glass door, reversible mounting
- Rack units: 20U
- Load capacity: 100 kg

- Assembled: yes
- Cabinet type: wall-mount enclosure
- Width: 600 mm