

## RZ Pro Rack with active ventilation by fans 800x1200x2100



<b>SKU</b>	RZ-S-8-12-42-V
<b>Produkt Verfügbarkeit</b>	
<b>Belastbarkeit in kg</b>	1600
<b>HE/U</b>	42
<b>Breite/width</b>	800
<b>Tiefe/depth</b>	1200
<b>Höhe/height</b>	2100
<b>kW</b>	
<b>Segmentation</b>	

### RZ Pro Rack

- Base frame, welded, with revolving round and slotted
- Static load capacity up to 1548 kg
- Infinitely depth-adjustable 19" mounting angles with 42 U
- Max. 19" mounting depth 1040 mm
- 1 x door with three-point locking and rotating lever handle, lockable
- Circumferential seal 3 x reciprocal hinges with 180° opening angle
- 1 x door made from solid steel with three-point locking and rotating lever handle, lockable
- Circumferential seal 3 x reciprocal hinges with 180° opening angle
- 2 x sidewall inserting screws
- Base with leveling feet - optional with transport wheels
- Removable hood with ventilation slots
- Removable cable entry panel Removable trim, side

- Roof module with cable inlet from brush strip and two blow off fans
- Powder coating RAL 9005 black ( also available: RAL7035 , light gray Item No. RZ -G -xx )
- Weight with packaging 198 kg ( 20 kg pack.)